

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	2	"global causal identifier"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/01/10 10:57
L2	6	uuid with log	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/01/10 10:57


[Web](#) [Images](#) [Groups](#) ^{New!} [News](#) [Froogle](#) [more »](#)

[Advanced Search](#)
[Preferences](#)

Web

 Results 1 - 10 of about 15,900 for **uuid log**. (0.38 seconds)

LogOps (Jini(TM) Technology Starter Kit v2.0.1Beta API ...

 ... void, uuidOp(**Uuid uuid**) **Log** the **Uuid** that identifies the space as a whole. ... public

 void uuidOp(**Uuid uuid**) **Log** the **Uuid** that identifies the space as a whole. ...

java.sun.com/products/jini/2.0.1/doc/api/com/sun/jini/outrigger/LogOps.html - 25k - [Cached](#) - [Similar pages](#)

Setting General Information Properties

 ... **UUID**, This 32-character, alphanumeric value represents the Universally Unique Identifier

 (**UUID**), which must contain only alphanumeric characters and be ... **Log** File. ...

helpnet.installshield.com/robo/projects/isxuniversalhelplibrary/topics/general_information_properties.htm - 10k -

[Cached](#) - [Similar pages](#)

Karsten Januszewski's UDDI Blog

 ... Odd Fact #3 - tModelKeys are prefixed with **uuid**: whereas all other keys in the UDDI

specification are simply a GUID, without the prefix . Why, you might ask? ...

www.gotdotnet.com/team/karstenj/blog.aspx - 50k - Jan 9, 2005 - [Cached](#) - [Similar pages](#)

DRAN Software - System Log Events Sorted By Source & Then By Event ...

 System **Log** Events Sorted By Source & Then By Event ID. Your Browser Does Not. ... RPC,

 1705, Error, The string universal unique identifier (**UUID**) is invalid.\r\n. ...

www.dransoft.com/Event_RPC.htm - 92k - [Cached](#) - [Similar pages](#)

ObjectRealms Repository - log - occams: versioning/trunk/uuid.py

... ago) by hazmat File length: 1200 byte(s) Diff to previous 28 - remove dependency

 archetypes (**uuid** func) - use ... Sort **log** by: Not sorted. ...

svn.objectrealms.net/view/occams/versioning/trunk/uuid.py?rev=164&view=log - 12k - [Cached](#) - [Similar pages](#)

ObjectRealms Repository - log - occams: versioning/trunk/uuid.py

... File length: 1200 byte(s) Diff to previous 28 , to selected 58 - remove dependency

 archetypes (**uuid** func) - use ... Sort **log** by: Not sorted. ...

svn.objectrealms.net/view/occams/versioning/trunk/uuid.py?rev=164&r1=58&view=log - 13k -

[Cached](#) - [Similar pages](#)
[\[More results from svn.objectrealms.net \]](#)

Accessing Blackboard through the CUNY Portal

 ... If you are still unable to **log** in please click on the "Portal Help" link on

 the left navigation bar and then click the link. ... **UUID** number. ...

www.qcc.cuny.edu/QCCOnline/Students/Blackboard61_login.htm - 72k - [Cached](#) - [Similar pages](#)

Microsoft Developer Studio Project File - Name="logdump" ...

 ... lib **uuid**.lib odbcc32.lib odbccp32.lib /nologo /subsystem:console /machine:I386 #

ADD LINK32 libfcgi.lib /nologo /pdb:none /machine:IX86 /out:"..\examples\log- ...

www.fastcgi.com/devkit/Win32/logdump.dsp - 5k - [Cached](#) - [Similar pages](#)

Benhui.net - Source for J2ME Bluetooth Mobile 3D MIDP 2.0 -

 ... c = null; 081 try 082 { 083 String url = "bt12cap://localhost:" + **uuid**.toString()

 +";name="+ appName+";ReceiveMTU=512;TransmitMTU=512"; 084 **log**("server url ...


www.benhui.net/modules.php?name=Bluetooth&page=L2CAP_Server.html - 48k - [Cached](#) - [Similar pages](#)

usr/bin/perl -w use strict; use Test::More tests => 7; BEGIN ...

 ... local to /trunk (base /trunk:5).', 'A fileb.txt', "New merge ticket: \$**uuid**:/local:

 6", 'Committed revision 7.']; is_output (\$svk, '**log**', ['-r7', '// x ...

search.cpan.org/src/CLKAO/SVK-0.26/t/07smerge-log.t - 4k - [Cached](#) - [Similar pages](#)



W b

Results 1 - 10 of about 3,350 for **uuid dce**. (0.06 seconds)**DCE 1.1: Remote Procedure Call - Universal Unique Identifier**

... If a **DCE** Security version **UUID** is being created, then replace the time_low field with the local user security attribute as defined by the **DCE**: Security ...

www.opengroup.org/onlinepubs/9629399/apdxa.htm - 20k - [Cached](#) - [Similar pages](#)

DCE H-Cells tools

... type isn't found. All **DCE** principals have a **uuid**, so I'm on the verge of paranoia by doing the error-checking. We can then put the ...

www.opengroup.org/dce/mall/dcecp-hcell.htm - 8k - [Cached](#) - [Similar pages](#)

[[More results from www.opengroup.org](#)]

DCE Glossary - What is a UUID?

... The timestamp component though is one of the reasons why **DCE** does not react well to clocks going backwards. A **UUID** may be generated using the uuidgen command ...

www.dsps.net/uuid.html - 4k - [Cached](#) - [Similar pages](#)

IBM Software - DFS - Interface UUID Problem with DFS 3.1

... 3.1 originated) bringing up **DCE** after restricting a network address or interface which was previously configured for use by **DCE** causes an invalid **uuid** to be ...

www-306.ibm.com/software/stormgmt/dfs/support/dfs_interface_uuid_problems.html - 24k - [Cached](#) - [Similar pages](#)

The DCE UUID Generator

Previous Next. The **DCE UUID** Generator. The **UUID** generator uuidgen is an interactive utility that creates UUIDs (universal unique identifiers). ...

support.entegrity.com/private/doclib/docs/osfhtm/develop/apgstyle/Apgsty11.htm - 2k - [Cached](#) - [Similar pages](#)

Comparing DCE and CORBA

... A **DCE** server may also generate what are called object type UUIDs, associate each object **UUID** with an object type **UUID**, and register a separate set of RPC ...

www.mitre.org/tech/domis/reports/DCEvCORBA.html - 40k - [Cached](#) - [Similar pages](#)

What Is DCE RPC?

... requests on. The **DCE** control program. The **DCE** control program (dcecp) is a tool for administering **DCE**. **UUID** facilities. These are ...

rsusu1.rnd.runnet.ru/alpha/progtool/dce31unx/overview/Dceint63.htm - 5k - [Cached](#) - [Similar pages](#)

OSSP: OSSP uuid

... API) and corresponding command line interface (CLI) for the generation of **DCE** 1.1 and ISO/IEC 11578:1996 compliant Universally Unique Identifiers (**UUID**). ...

www.ossip.org/pkg/lib/uuid/ - 31k - [Cached](#) - [Similar pages](#)

QUuid Class

... Returns a new **UUID** of **DCE** variant, and Random type. ... Returns the version of the **UUID**, if the **UUID** is of the **DCE** variant; otherwise returns VerUnknown. ...

doc.trolltech.com/3.3/quuid.html - 12k - [Cached](#) - [Similar pages](#)

IBM DCE Version 3.1 for AIX and Solaris: Application Development ...

... a client and server. (Using the **DCE** Name Service also shows the object **UUID** as part of the binding information. This applies to ...

zivunix.uni-muenster.de/DCEdoc/APGSTYLE/APGSTY09.HTM - 36k - [Cached](#) - [Similar pages](#)